

## POWERFIT SINGLE POLE CONNECTOR

500A

### LINE DRAIN

**KUPO®**

#### Features

- \* Brass contact with silver plating ensures excellent conductivity
- \* Ergonomic rubber grip enhances handling comfort and safety
- \* Durable thermoplastic body offers superior impact resistance and electrical insulation
- \* O-ring provides an excellent protection against water and dust ingress after mating
- \* M40\*1.5 cable gland with rubber bushing for secure IP67-rated sealing



**Item Number:** PFLD-3GY-S150M40A

Phase: Line 3

Color: Gray

Type: Double Set Screws (for 150mmsq cable)

Cable Gland (Standard): M40/CG-M4015-32



Type Approved  
Safety  
Regular Production  
Surveillance

www.tuv.com  
ID 1111303479

#### Material Information

Connector Body: Non-conductive high impact-resistant thermoplastic

Contact Material: Brass (silver-plated)

O-Ring: Silicone

Cable Gland & Bushing: Nylon, Rubber & Silicone

#### Electrical Information

Amperage Rating: 500A Maximum

Voltage Rating: 1000V AC/DC Maximum

Test Voltage: 4500V AC

Short Circuit Rating: Up to 35.5kA

Insulation Resistance: > 5000M Ohms at 500V AC

Contact Resistance: 0.1m Ohms



#### Mechanical Information

Contact Type: Set screw

Set Screw Torque: 10.5 N/meter (minimum required)

Connection Type: Push-and-twist

Cable Gland Size: M40 x 1.5 with sealing bushing (Inner Diameter: 14-22 mm and 23-33 mm)

Mating Cycle: 500

#### Environmental Information


Ingress Protection: IP67 rating while mated

Flammability: UL94-V0 (body material rating)

Working Temperature: -25 to 125 Celsius Degree

Certifications: TÜV, CE, RoHS and REACH compliant









#### Dimensions



unit : mm

- Specifications subject to change without notice.
- [www.stage.com.tw](http://www.stage.com.tw)

2026 V1



# KUPO®

© 2026 KUPO All rights reserved.

KUPO Shanghai Co., Ltd.

Address: Building 66, No. 2050 Dingsheng Rd.,

Songjiang District, Shanghai, China

Websites: kupopower.com / kupopower.com.cn

This document is provided for reference purposes only. It is not intended for use as a construction, installation, or fabrication drawing. KUPO shall not be liable for any loss or damage arising from the use of this document for such purposes.

These files may not be reproduced, distributed, or made available to third parties without prior written permission from KUPO.

KUPO Powerfit connectors are designed to be compatible and intermateable with other ITT Powerlock style connectors such as P3 Powersafe and Ten47 Powerline.

UNLESS OTHERWISE SPECIFIED

DIMENSIONS ARE IN MILLIMETERS

DO NOT SCALE

ORG. SCALE

NTS

CREATE DATE:

10/Aug/2026

MATERIAL

HOUSING: Non-conductive, high-impact-resistant thermoplastic, UL 94 V-0  
CONTACT: Silver-plated brass

TITLE

500A POWERFIT LINE DRAIN CONNECTOR

DWG. NO.

KPFLD500

ISSUE NO.

1



CB UK CA CE

