POWERFIT SINGLE POLE CONNECTOR

400A

LINE SOURCE

Features
* Innovative key-release pin allows for fast and convenient disconnection
* Copper contact with silver plating ensures excellent conductivity
* Ergonomic rubber grip enhances handling comfort and safety
* Durable thermoplastic body offers superior impact resistance and electrical insulation
* M40*1.5 cable gland with rubber bushing for secure IP67-rated sealing

Item Number: PFLS-2O-S120M40A
Phase: L2
Color: Orange
Type: Double Set Screws (for 120mmsq cable)
Cable Gland: M40A

Type Approved
Safety
Regular Production
Surveillance
TÜVRheinland
CERTIFIED
www.tuv.com
ID 1111304988

Material Information
Connector Body: Non-conductive high impact-resistant thermoplastic
Contact Material: Brass (silver-plated)
Cable Gland: Nylon
Bushing：Rubber and Silicone




Electrical Information
Amperage Rating: 400A Maximum
Voltage Rating: 1000V AC/DC Maximum
Test Voltage: 4500V AC
Rated Short-Time Withstand Current (Icw): 16 kA /1 s (RMS)
Rated Short-Circuit Peak Current (Ipk): 35.5 kA (Peak)
Insulation Resistance: > 5000M Ohms at 500V AC
Contact Resistance: 0.1m Ohms


Mechanical Information
Contact Type: Set screw
Connection Type: Push-and-twist with key release mechanism
Cable Gland Size: M40 x 1.5 with sealing bushing
Inner Diameter(Standard) 14-22 mm and 23-33mm
Mating Cycle: 500


Environmental Information
Ingress Protection: IP67 rating while mated
Flammability: UL94-V0 (body material rating)
Working Temperature: -25 to 125 °C
Certifications: TÜV, CE, RoHS and REACH compliant

Dimensions





unit : mm






A-A








PF-PS-M



PF-R120



CG-M4015-32

© 2026 KUPO All rights reserved.
KUPO Shanghai Co., Ltd.
Address: Building 66, No. 2050 Dingsheng Rd.,
Songjiang District, Shanghai, China
Websites: kupopower.com / kupopower.com.cn

This document is provided for reference purposes only. It is not intended for use as a construction, installation, or fabrication drawing. KUPO shall not be liable for any loss or damage arising from the use of this document for such purposes.

These files may not be reproduced, distributed, or made available to third parties without prior written permission from KUPO.

KUPO Powerfit connectors are designed to be compatible and intermateable with other ITT Powerlock style connectors such as P3 Powersafe and Ten47 Powerline.

UNLESS OTHERWISE SPECIFIED

DIMENSIONS ARE IN MILLIMETERS

DO NOT SCALE

ORG. SCALE	CREATE DATE.
NTS	10/Aug/2026

MATERIAL

HOUSING: Non-conductive, high-impact-resistant thermoplastic, UL 94 V-0
CONTACT: Silver-plated brass

TITLE

400A POWERFIT LINE SOURCE CONNECTOR

DWG. NO.	ISSUE NO.
KPFLS400	1